



BRIGHT PEOPLE'S CHOICE



BM062

Compact DC/AC
Clamp-on Multimeter

30ms MAX HOLD	Captures Peak In-Rush Current As Short As 30ms In Duration
DATA HOLD	Freezes The Displaying Reading For Later Viewing
BATTERY COMPARTMENT	With Access Door For Easy Battery Replacement
PROBE HOLDERS	Built-In Probe Storage Holders
RELATIVE ZERO MODE	For Convenient Readings Comparison & DCA Zero Adjustment
LARGE EASY-TO-READ LCD DIGITS	With 3/sec Nominal Update Rate
HIGH VOLTAGE (ACV) Hz	Measures Noisy High Voltage ACV Frequency VIA Test Leads
DIODE TEST	For Testing Diodes And Rectifiers
CAPACITANCE	6 Ranges; Auto-Ranging Up To 3000 μ F With 600V Protection
AUDIBLE CONTINUITY	For Quick Open-Short Tests On Switches, Fuses, And Wires
RESISTANCE	6 Ranges; Auto-Ranging Up To 40Mega OHMS With 600V Protection
TRANSIENT PROTECTION	Up To 6.5kV 1.2/50 μ s Lightning Surge; More Confidence For Serious Users
EMC	Meets EN61326-1:2006 (EN55011, EN61000-3-2/-3 & EN61010-4-2/-3/-4/-5/-6/-8/-11)
AC 400 AMPS MEASUREMENTS	Non-Invasive AC Current VIA Clamp Jaws; Best Resolution 0.1A
DC 400 AMPS MEASUREMENTS	Non-Invasive DC Current VIA Clamp Jaws; Best Resolution 0.1A
5 FULL AC VOLTAGE RANGES	From 400mV Range Up To 600 V Range
5 FULL DC VOLTAGE RANGES	From 400mV Range Up To 600 V Range
FUNCTION SELECTION	Conveniently Toggle Between Primary & Secondary Functions
DISPLAY BACKLIGHT	For Easy Viewing In The Dark
HIGH SPEED AUTO-RANGING	Shortens The Time To Test And Increases The Ease Of Use
TRUE RMS	For Non-Sinusoidal Waveforms Of AC Voltages & AC Currents
LVD CAT III 600V SAFETY	Meets EN61010-1 & EN61010-2-032 2nd Edition CAT III 600V
RUGGED & DURABLE	High-Impact Fire-Retarded Enclosure For Reinforced Safety & Reliability
SMALL DCA/ACA CLAMP JAWS	For Easy Access To Tight Places With 400A DC/AC Capability
STYLISH & HANDY	Also Comes With A Soft Pouch For Easy Carrying & Protection