



BRIGHT PEOPLE'S CHOICE

**BM077**

AmpTip Jaws  
Clamp-on DMM



RESISTANCE	3 Auto-Ranges Up To 60kΩ Best Resolution 0.1Ω At 600Ω Range
ERGONOMIC & STREAMLINE BODY	Also Comes With A Soft Pouch For Easy Carrying & Protection
1.0% DCV BASIC ACCURACY	DCV Up To 600V; ACV Up To 600V
RELATIVE ZERO & DC_ZERO	For Convenient Readings Comparison As Well As DC Jaws Hysteresis Offset
DATA HOLD	Freezes The Displaying Reading For Later View
RUGGED & DURABLE	High-Impact Fire-Retarded Enclosure With Battery Compartment & Access Door
TRANSIENT PROTECTION	Up To 6kV 1.2/50μs Lightning Surge; More Confidence For Serious Users
EMC	Meets EN61326-1:2006(EN55022, EN61000-3-2/-3 & EN61000-4-2/-3/-4/-5/-6/-8/-11 )
RECORD MAX / MIN / AVG	Records Max, Min, & Calculates AVG Readings Over Time. Auto-Ranging
AUTO-POWER-OFF	Extends Battery Life
FULLY AUTO-RANGING DMM	Shortens The Time To Measure And Increases The Ease Of Use
VFD V & Hz FEATURE	Measures Fundamental Voltage & Frequency Of Most Variable Frequency Drives
AmpTip LOW-CURRENT & Hz	Ergonomically Measures At Jaw Tip For Small-Sized Conductors Up To 60 Amps
REGULAR CURRENT & Hz	Measures At Jaw Center For Regular Conductors Up To 600 Amps
FAST AUDIBLE CONTINUITY	For Quick Open-Short Tests On Switches, Fuses, And Wires
DIODE TEST	For Testing Diodes & Rectifiers
LVD CAT III 600V & CAT IV 300V	Certified EN61010-2-032, EN61010-2-032, EN61010-1 & Relevant UL Standards On CAT III 600V & CAT IV 300V
HANDY 35mm AmpTip CLAMP JAWS	For Large & Small Conductors With AC Or DC TRMS 600A Capability
EF-DETECTION	Both Non-Contact (NCV) & Single-Probe Voltage Detection For Identifying Live Lines