



BRIGHT PEOPLE'S CHOICE

BM078

AmpTip Jaws
Clamp-on DMM



CAPACITANCE

2 Auto-Ranges Up To 2500 μ F
To Measure Motor Capacitors

RESISTANCE

3 Auto-Ranges Up To 60k Ω
Best Resolution 0.1 Ω At 600 Ω Range

ERGONOMIC & STREAMLINE BODY

Also Comes With A Soft Pouch
For Easy Carrying & Protection

1.0% DCV BASIC ACCURACY

DCV Up To 600V;
ACV Up To 600V

RELATIVE ZERO & DC_ZERO

For Convenient Readings Comparison
As Well As DC Jaws Hysteresis Offset

DATA HOLD

Freezes The Displaying
Reading For Later View

RUGGED & DURABLE

High-Impact Fire-Retarded
Enclosure With Battery
Compartment & Access Door

TRANSIENT PROTECTION

Up To 6kV 1.2/50 μ s Lightning Surge;
More Confidence For Serious Users

EMC

Meets EN61326-1:2006(EN55022,
EN61000-3-2/-3 & EN61000-4-2/-3/-4/-5/-6/-8/-11
)

BACKLIGHTED LCD DISPLAY

For Easy Viewing In The Dark

RECORD MAX / MIN / AVG

Records Max, Min, & Calculates AVG
Readings Over Time. Auto-Ranging

IN-RUSH PEAK- RMS

Captures In-Rush Peak RMS Readings
At Durations As Short As 80ms

AUTO-POWER- OFF

Extends Battery Life

FULLY AUTO- RANGING DMM

Shortens The Time To Measure
And Increases The Ease Of Use

VFD V & Hz FEATURE

Measures Fundamental
Voltage & Frequency Of Most
Variable Frequency Drives

AmpTip LOW- CURRENT & Hz

Ergonomically Measures At Jaw Tip For
Small-Sized Conductors Up To 60 Amps

REGULAR CURRENT & Hz

Measures At Jaw Center For
Regular Conductors Up To 600 Amps

FAST AUDIBLE CONTINUITY

For Quick Open-Short Tests
On Switches, Fuses, And Wires

DIODE TEST

For Testing Diodes & Rectifiers

LVD CAT III 600V & CAT IV 300V

Certified EN61010-2-032, EN61010-2-032,
EN61010-1 & Relevant UL Standards On
CAT III 600V & CAT IV 300V

AC+DC TRUE RMS MEASUREMENTS

For Non-Sinusoidal & Complex
Waveforms Of Voltages & Currents

HANDY 35mm AmpTip CLAMP JAWS

For Large & Small Conductors With
AC Or DC+AC TRMS 600A Capability

EF-DETECTION

Both Non-Contact (NCV) &
Single-Probe Voltage Detection
For Identifying Live Lines