



BRIGHT PEOPLE'S CHOICE

BM079

AmpTip Jaws
Clamp-on DMM



DC μ A

PHASE ROTATION

CAPACITANCE

RESISTANCE

ERGONOMIC & STREAMLINE BODY

1.0% DCV BASIC ACCURACY

RELATIVE ZERO & DC_ZERO

DATA HOLD

RUGGED & DURABLE

TRANSIENT PROTECTION

EMC

BACKLIGHTED LCD DISPLAY

RECORD MAX / MIN / AVG

IN-RUSH PEAK-RMS

AUTO-POWER-OFF

FULLY AUTO-RANGING DMM

VFD V & Hz FEATURE

AmpTip LOW-CURRENT & Hz

REGULAR CURRENT & Hz

FAST AUDIBLE CONTINUITY

DIODE TEST

LVD CAT III 600V & CAT IV 300V

AC+DC TRUE RMS MEASUREMENTS

TYPE-K TEMPERATURE

HANDY 35mm AmpTip CLAMP JAWS

EF-DETECTION

For HVAC Flame Sensors Testing Via Test Probes

Dual Sensitivity Modes For Both Motors And Supply Systems

2 Auto-Ranges Up To 2500 μ F To Measure Motor Capacitors

3 Auto-Ranges Up To 60k Ω Best Resolution 0.1 Ω At 600 Ω Range

Also Comes With A Soft Pouch For Easy Carrying & Protection

DCV Up To 600V; ACV Up To 600V

For Convenient Readings Comparison As Well As DC Jaws Hysteresis Offset

Freezes The Displaying Reading For Later View

High-Impact Fire-Retarded Enclosure With Battery Compartment & Access Door

Up To 6kV 1.2/50 μ s Lightning Surge; More Confidence For Serious Users

Meets EN61326-1:2006(EN55022, EN61000-3-2/-3 & EN61000-4-2/-3/-4/-5/-6/-8/-11)

For Easy Viewing In The Dark

Records Max, Min, & Calculates AVG Readings Over Time. Auto-Ranging

Captures In-Rush Peak RMS Readings At Durations As Short As 80ms

Extends Battery Life

Shortens The Time To Measure And Increases The Ease Of Use

Measures Fundamental Voltage & Frequency Of Most Variable Frequency Drives

Ergonomically Measures At Jaw Tip For Small-Sized Conductors Up To 60 Amps

Measures At Jaw Center For Regular Conductors Up To 600 Amps

For Quick Open-Short Tests On Switches, Fuses, And Wires

For Testing Diodes & Rectifiers

Certified EN61010-2-032, EN61010-2-032, EN61010-1 & Relevant UL Standards On CAT III 600V & CAT IV 300V

For Non-Sinusoidal & Complex Waveforms Of Voltages & Currents

Selectable $^{\circ}$ C And $^{\circ}$ F Readings; Comes With Bkp60 Bead Probe

For Large & Small Conductors With AC Or DC+AC TRMS 600A Capability

Both Non-Contact (NCV) & Single-Probe Voltage Detection For Identifying Live Lines