



BRIGHT PEOPLE'S CHOICE



BM117

AutoCheck DMM

DATA HOLD

Freezes The Displaying Reading For Later Viewing

BATTERY COMPARTMENT

With Access Door For Easy Battery Replacement

PROBE HOLDERS

Built-In Probe Storage Holders

ELECTRIC FIELD EF-DETECTION

Features Both Non-Contact & Probe Contact EF-Detection For Tracing Live Wiring

AUTOCHECK FEATURE

Automatic Selection Of LoZ DCV, LoZ ACV & OHMS

GHOST-VOLTAGE-BUSTER

LoZ Drains Ghost/Stray Voltages Leaving Only Hard Signals On Meter Readings

AUTOCHECK-RESISTANCE

4 Ranges; Auto-Ranging Up To 6 MΩ

CAPACITANCE

5 Ranges; Auto-Ranging Up To 2000μF With 600V Protection

DIODE TEST

For Testing Diodes And Rectifiers

600 OHMS RANGE WITH AUDIBLE CONTINUITY

For Low Resistance & Quick Open-Short Tests On Switches, Fuses, And Wires

TRANSIENT PROTECTION

Up To 6.5kV 1.2/50μs Lightning Surge; More Confidence For Serious Users

EMC

Meets EN61326(1997, 1998/A1), EN61000-4-2(1995), & EN61000-4-3(1996)

UP TO AC 2000 AMPS MEASUREMENTS

2 Non-Invasive AC Current Auto-Ranges VIA Clamp Jaws; Best Resolution 0.1A

HIGH VOLTAGE Hz

Measures Noisy High Voltage ACV Frequencies VIA Test Leads

HIGH IMPEDANCE VOLTAGE

600VAC/DC Measuring Capabilities; High Input Impedance For Load Sensitive Circuits

0.5% DCV BASIC ACCURACY

3 Ranges; Auto-Ranging Up To 600 Volts, 0.1V Resolution

LVD CAT III 600V SAFETY

Meets EN61010-2-032 CAT III 600V

RUGGED & DURABLE

High-Impact Fire-Retarded Enclosure For Reinforced Safety & Reliability

LARGE U-SHAPE CLAMP JAWS

Measure ACA Of Large Single Conductor Or Differential ACA Of Multiple Conductors

EF ANTENNA

Conveniently Located At The Jaw Tip For Non-Contact EF-Detection (NCV)

STYLISH & HANDY

Also Comes With A Soft Pouch For Easy Carrying & Protection