



BRIGHT PEOPLE'S CHOICE



## BM118

AutoCheck DMM

### DATA HOLD

Freezes The Displaying Reading For Later Viewing

### BATTERY COMPARTMENT

With Access Door For Easy Battery Replacement

### PROBE HOLDERS

Built-In Probe Storage Holders

### ELECTRIC FIELD EF-DETECTION

Features Both Non-Contact & Probe Contact EF-Detection For Tracing Live Wiring

### AUTOCHECK FEATURE

Automatic Selection Of LoZ DCV, LoZ ACV & OHMS

### GHOST-VOLTAGE-BUSTER

LoZ Drains Ghost/Stray Voltages Leaving Only Hard Signals On Meter Readings

### AUTOCHECK-RESISTANCE

4 Ranges; Auto-Ranging Up To 6 MΩ

### CAPACITANCE

5 Ranges; Auto-Ranging Up To 2000μF With 600V Protection

### DIODE TEST

For Testing Diodes And Rectifiers

### 600 OHMS RANGE WITH AUDIBLE CONTINUITY

For Low Resistance & Quick Open-Short Tests On Switches, Fuses, And Wires

### TRANSIENT PROTECTION

Up To 6.5kV 1.2/50μs Lightning Surge; More Confidence For Serious Users

### EMC

Meets EN61326(1997, 1998/A1), EN61000-4-2(1995), & EN61000-4-3(1996)

### UP TO AC 2000 AMPS MEASUREMENTS

2 Non-Invasive AC Current Auto-Ranges VIA Clamp Jaws; Best Resolution 0.1A

### HIGH VOLTAGE Hz

Measures Noisy High Voltage ACV Frequencies VIA Test Leads

### HIGH IMPEDANCE VOLTAGE

600VAC/DC Measuring Capabilities; High Input Impedance For Load Sensitive Circuits

### DISPLAY BACKLIGHT

For Easy Viewing In The Dark

### TRUE RMS MEASUREMENTS

For Non-Sinusoidal Waveforms Of AC Voltages & AC Currents

### 0.5% DCV BASIC ACCURACY

3 Ranges; Auto-Ranging Up To 600 Volts, 0.1V Resolution

### LVD CAT III 600V SAFETY

Meets EN61010-2-032 CAT III 600V

### RUGGED & DURABLE

High-Impact Fire-Retarded Enclosure For Reinforced Safety & Reliability

### LARGE U-SHAPE CLAMP JAWS

Measure ACA Of Large Single Conductor Or Differential ACA Of Multiple Conductors

### EF ANTENNA

Conveniently Located At The Jaw Tip For Non-Contact EF-Detection (NCV)

### STYLISH & HANDY

Also Comes With A Soft Pouch For Easy Carrying & Protection