



BM112s Versatile Clamp-on Multimeter

## 30ms MAX HOLD

DATA HOLD

## LIGHT WEIGHT & SMALL BODY HIGH CURRENT

(ACA) Hz HIGH VOLTAGE (ACV) Hz

FAST AUDIBLE CONTINUITY

CAPACITANCE

DIODE TEST

RESISTANCE

TRANSIENT PROTECTION

EMC

0.5% DCV & ACV BASIC ACCURACY

ENLARGED SINGLE DISPLAY TRUE RMS

MEASUREMENTS FULLY AUTO-

RANGING DMM RELATIVE ZERO

RUGGED &

DURABLE LVD CAT III 600V SAFETY

SMALL & ULTRA-SLIM CLAMP JAWS

## Captures In-Rush RMS Values Of ACA Or ACV As Short As 30ms In Duration Freezes The Displaying Reading For Later View

Also Comes With A Soft Pouch For Easy Carrying & Protection

Measures Non-Invasive ACA Frequency VIA Clamp Jaws

Measures Noisy High Voltage ACV Frequency VIA Test Leads

For Quick Open-Short Tests On Switches, Fuses, And Wires

6 Auto-Ranges Up To 3000µF To Measure Motor Capacitors

For Testing Diodes & Rectifiers

6~Auto-Ranges Up To  $40 M\Omega$  With 600 V Protection

Up To 6kV 1.2/50µs Lightning Surge; More Confidence For Serious Users

Meets EN61326(1997, 1998/A1), EN61000-4-2(1995, 2000/A2), & EN61000-4-3(2002)

DCV 5 Auto-Ranges To 600V; ACV 4 Auto-Ranges To 600V

Enlarged Display Digits For Single Display Models

For Non-Sinusoidal Waveforms Of AC Voltages & AC Currents

Shortens The Time To Measure And Increases The Ease Of Use

For Convenient Readings Comparison & Zero Offset

High-Impact Fire-Retarded Enclosure For Reinforced Safety & Reliability Meets Both EN61010-2-032 CAT III 600V & UL61010B-2-032 CAT III 600V On All Models

For Easy Access To Tight Places With AC 600A Capability