



BM127s

Versatile Clamp-on Multimeter

30ms MAX HOLD Capture

DATA HOLD

LIGHT WEIGHT & SMALL BODY

HIGH VOLTAGE (ACV) Hz

FAST AUDIBLE CONTINUITY

CAPACITANCE

DIODE TEST RESISTANCE

TRANSIENT PROTECTION

FMC

µA FUNCTION

TYPE-K TEMPERATURE

0.5% DCV & ACV BASIC ACCURACY

TWIN DISPLAYS

FULLY AUTO-RANGING DMM

RUGGED & DURABLE

LVD CAT III 600V SAFETY

SMALL & ULTRA-SLIM CLAMP JAWS Captures In-Rush RMS Values Of ACA Or ACV As Short As 30ms In Duration

Freezes The Displaying Reading For Later View

Also Comes With A Soft Pouch For Easy Carrying & Protection

Measures Noisy High Voltage ACV Frequency VIA Test Leads

For Quick Open-Short Tests On Switches, Fuses, And Wires

6 Auto-Ranges Up To 3000µF To Measure Motor Capacitors For Testing Diodes & Rectifiers

6 Auto-Ranges Up To 40MΩ With 600V Protection

Up To 6kV 1.2/50µs Lightning Surge; More Confidence For Serious Users

Meets EN61326(1997, 1998/A1), EN61000-4-2(1995, 2000/A2), & EN61000-4-3(2002)

3(2002)

For HVAC Flame Sensors Testing VIA Test Leads With 600V Protection

Selectable °C And °F Readings; Comes With BKP60 Bead Probe

DCV 5 Auto-Ranges To 600V; ACV 4 Auto-Ranges To 600V

Simultaneous Measurements Of A+V, A+OHMS, ...ETC

Shortens The Time To Measure And Increases The Ease Of Use

High-Impact Fire-Retarded Enclosure For Reinforced Safety & Reliability

Meets Both EN61010-2-032 CAT III 600V & UL61010B-2-032 CAT III 600V On All Models

For Easy Access To Tight Places With AC 600A Capability