



BRIGHT PEOPLE'S CHOICE



BM131
LoggerClamp

AUTO-HOLD	Automatically Captures & Displays Significant Stable Readings
DATA HOLD	Freezes The Displaying Reading For Later View
BATTERY COMPARTMENT	With Access Door For Easy Battery Replacement
PROBE HOLDERS	Built-In Probe Storage Holders
5400 MINUTES Hi-Lo LOGGING	Logs V Or A Surge (Hi) & SAG (Lo) Of Every 1 Minute Interval At Sampling Speed < 50ms
HIGH CURRENT Hz	Measures Non-Invasive ACA Frequency VIA Clamp Jaws
HIGH VOLTAGE Hz	Measures Noisy High Voltage ACV Frequencies VIA Test Leads
250µs FAST AUDIBLE CONTINUITY	For Quick Open-Short Tests On Switches, Fuses, And Wires
RESISTANCE	Up To 999.9 OHMS, 0.1 OHM Resolution With 600V Protection
TRANSIENT PROTECTION	Up To 6.5kV 1.2/50µs Lightning Surge; More Confidence For Serious Users
EMC	Meets EN61326(1997, 1998/A1), EN61000-4-2(1995), & EN61000-4-3(1996)
UP TO AC 1000 AMPS MEASUREMENTS	3 Non-Invasive AC Current Ranges VIA Clamp Jaws; Best Resolution 0.01A
TEMPERATURE	Type-K Measurement; Selectable °C Or °F Readings; Comes With BKP60 Bead Probe
0.5% DCV BASIC ACCURACY	Up To 600 Volts, 0.1V Resolution
PC-COMM INTERFACE CABILITIES	Built-In Optical Isolated Data Output Port. Optional Purchase Interface Kit For PC Connection
LOGGED DATA RECALL	Up/Down Quick View Of Hi-Lo Data On LCD. No Computer Is Required
LVD CAT III 600V SAFETY	Meets EN61010-2-032 CAT III 600V
RUGGED & DURABLE	High-Impact Fire-Retarded Enclosure For Reinforced Safety & Reliability
LARGE U-SHAPE CLAMP JAWS	Measure ACA Of Large Single Conductor Or Differential ACA Of Multiple Conductors
STYLISH & HANDY	Also Comes With A Soft Pouch For Easy Carrying & Protection