



BRIGHT PEOPLE'S CHOICE



BM132
LoggerClamp

- AUTO-HOLD** Automatically Captures & Displays Significant Stable Readings
- DATA HOLD** Freezes The Displaying Reading For Later View
- BATTERY COMPARTMENT** With Access Door For Easy Battery Replacement
- PROBE HOLDERS** Built-In Probe Storage Holders
- 5400 MINUTES Hi-Lo LOGGING** Logs V Or A Surge (Hi) & SAG (Lo) Of Every 1 Minute Interval At Sampling Speed < 50ms
- HIGH CURRENT Hz** Measures Non-Invasive ACA Frequency VIA Clamp Jaws
- HIGH VOLTAGE Hz** Measures Noisy High Voltage ACV Frequencies VIA Test Leads
- 250µs FAST AUDIBLE CONTINUITY** For Quick Open-Short Tests On Switches, Fuses, And Wires
- RESISTANCE** Up To 999.9 OHMS, 0.1 OHM Resolution With 600V Protection
- TRANSIENT PROTECTION** Up To 6.5kV 1.2/50µs Lightning Surge; More Confidence For Serious Users
- EMC** Meets EN61326(1997, 1998/A1), EN61000-4-2(1995), & EN61000-4-3(1996)
- UP TO AC 1000 AMPS MEASUREMENTS** 3 Non-Invasive AC Current Ranges VIA Clamp Jaws; Best Resolution 0.01A
- TEMPERATURE** Type-K Measurement; Selectable °C Or °F Readings; Comes With BKP60 Bead Probe
- 0.5% DCV BASIC ACCURACY** Up To 600 Volts, 0.1V Resolution
- DISPLAY BACKLIGHT** For Easy Viewing In The Dark
- WIDE ACV & ACA BAND-WIDTH** Up To 3.1KHz AC Band-Width To Measure More True RMS Details
- TRUE RMS MEASUREMENTS** For Non-Sinusoidal Waveforms Of AC Voltages & AC Currents
- PC-COMM INTERFACE CABILITIES** Built-In Optical Isolated Data Output Port. Optional Purchase Interface Kit For PC Connection
- LOGGED DATA RECALL** Up/Down Quick View Of Hi-Lo Data On LCD. No Computer Is Required
- LVD CAT III 600V SAFETY** Meets EN61010-2-032 CAT III 600V
- RUGGED & DURABLE** High-Impact Fire-Retarded Enclosure For Reinforced Safety & Reliability
- LARGE U-SHAPE CLAMP JAWS** Measure ACA Of Large Single Conductor Or Differential ACA Of Multiple Conductors
- STYLISH & HANDY** Also Comes With A Soft Pouch For Easy Carrying & Protection