



BRIGHT PEOPLE'S CHOICE

BM137ma

Patented AmpTip™ Jaws
Clamp-on DMM

PATENTED AmpTip™ CLAMP JAWS

LVD CAT III 600V & CAT IV 300V

REGULAR CURRENT

0.001A Hi-res AmpTip™ JAWS

1.0% DCV BASIC ACCURACY

DIRECT LPF ACV & Hz FOR VFD

BACKLIGHTED LCD DISPLAY

FULLY AUTO-RANGING

INTELLIGENT AUTO-POWER-OFF (APO)

ERGONOMIC & STREAMLINE BODY

TRUE RMS MEASUREMENTS

RUGGED & DURABLE

EMC

DUAL SENSITIVITIES EF-DETECTION

MAX CONDUCTOR SIZE 26mm, 200Amps

MAX HOLD

INNOVATIVE BeepLit™ DIODE TEST

RELATIVE ZERO & DC_ZERO

DATA HOLD

DCµA

TYPE-K TEMPERATURE

CAPACITANCE

INNOVATIVE BeepLit™ CONTINUITY

RESISTANCE

TRANSIENT PROTECTION

Easy Access & Excellent Repeatability For Measuring Thin Conductors In Tight Areas

Certified EN61010-2-032, EN61010-1 & Relevant Standards On CAT III 600V & CAT IV 300V

Measures At Jaw Center For Regular Conductors Up To 200 Amps

Accurate to Milliamp Levels for Electronic Devices

Measures Up To 600V DC; 60V DC Range Added

Measures Voltage & Frequency Of Most Variable Frequency Drives And Noisy Electrical Signals Up To 600V AC

For Easy Viewing In The Dark

Shortens The Time To Measure And Increases The Ease Of Use

Stays ON While In Measurements; Intelligently Turns OFF To Extend Battery Life

Body width <50mm Fits Nicely In A Hand Overall Length <190mm For Easy Carrying

For Non-sinusoidal & Complex Waveforms Of Voltages & Currents

Robust Enclosure; Precise & Reliable Rotary Switch; Premium Plating & Low Leakage PCB

Superior Immunity To Interference; Reliable Operations And Readings; Meets The Latest EN61326-1

Features Non-Contact (NCV) & Single-Probe Voltage Detection For Identifying Live Lines; Added User Selectable Hi/Lo Sensitivities

Features 200A AC/DC Hall-effect Jaws with High Resolution Technology

Update rate is boosted to 40/s to capture surges in the Voltage & Current functions

Short-Beep Alert On Forward Voltages <0.85V; Beep & Backlight Effects For Shorted Diodes

REL For Convenient Readings Comparison; DC_Zero For DCA Residue Offset

Freezes The Displaying Reading For Later View

For HVAC Flame Sensors Testing Via Test Probes

Selectable °C And °F Readings; Comes With Bkp60 Bead Probe

2 Auto-ranges Up To 2500µF To Measure Motor Capacitors

Quick Open-short Tests On Switches And Wires; Beep & Backlight Effects For Noisy Environments

Best Resolution 0.1Ω At 600Ω Range; 2 Auto-ranges Up To 6kΩ (BM135ma); 5 Auto-ranges Up To 6000kΩ (BM137ma)

Up To 6kV 1.2/50µs Lightning Surge; Fully Certified By Independent Test Lab; Years Of Credibility For Serious Users

