

Duo-core Dual Measurements A + V, VFD, HVAC, RST, AmpTip™ & Much More!

Convenient Measurements Of Amps + A DMM Function!

Large Ohms, DC μ A & Temperature For HVAC!

Patented AmpTip™ Jaws For Thin Conductors!

Patented 3-Terminal RST For Power & Motors!

EF-Detection (NCV) With Hi/Lo Sensitivities!

+Visible Continuity For Noisy Environments!

Measures VFD V/Hz With Low Pass Filter!

Peak-RMS To Capture In-rush Currents!

World-wide Patented:

I442059

D148257

1996509

D678091S

402011006274.7

M438628

2755507

13486915

202012102140.4

M429871

2359464

202011052429.9



BM170D Series

Convenient Clamp DMM Duo



BRIGHT PEOPLE'S CHOICE
<http://www.brymen.com>



● **BM176D**



● **BM175D**



● **BM173D**

176D	175D	173D	Functions & Features
●	●	●	VFD-V & Hz For Fundamental V/Hz Of Most Variable-Frequency-Drives
●	●	●	Fast Measurement Updates 5/Sec
●	●	●	Dual 3-5/6 Digits 6,000 Counts Large LCD Display
●	●	●	Duo-Core To Simultaneously Measure Clamp-On Amps + A DMM Function
●	●	●	30mm Conductor Size Ultra-Slim 600A AC Jaws
●	●	●	AmpTip™ Low-Current-Range Calibrated At Jaw-Tip For Slim-Conductors
●	●	●	AC True RMS Voltage And Current Functions
●	●	●	Intelligent Auto Power Off
●	●	●	Data HOLD
●	●	●	Fast 80ms PEAK-RMS Mode To Capture In-Rush Currents
●	●	●	Back-Lighted Easy-To-Read LCD Display
●	●	●	Non-Contact EF-Detection (NCV), Selectable Hi/Lo Sensitivities
●	●	●	Probe-Contact EF-Detection For More Precise Indication Of Live
●			Ⓡ 3Φ-Rotation-R For Supply Systems (Probe-Contact)
●			Ⓢ 3Φ-Rotation-M (Hi-Sensitivity Mode) For Motors (Probe-Contact)
●	●		Type-K Temperature -10.0°C To 400°C Or 14.0°F To 752°F Selectable
●	●		DCμA Ranges 200.0μA To 2000μA (Via Leads) For HVAC Flame Sensors
●	●	●	ACA Ranges 60.00A To 600.0A + AmpTip™ ACA 60.00A Range
●	●	●	DCV Range 600.0V
●	●	●	ACV Range 600.0V
●	●	●	Ohm Ranges 600.0Ω To 6000kΩ
●	●	●	Cx Ranges 200.0μF To 2500μF For Start & Run Motor Capacitors
●	●	●	Diode Test
●	●	●	Fast Audible+Visible Continuity
●	●	●	Line-Level ACV Frequency 10.00Hz To 999.9Hz
●	●	●	Soft Carrying Pouch
●	●	●	Rugged Fire Retarded Casing With Battery Access Door
●	●	●	Transient Protection 6kV 1.2/50μS Lightning Surge
●	●	●	LVD EN61010-2-032 & EN61010-1 CAT III 600V & CAT IV 300V
●	●	●	EMC EN61326-1:2013

Convenient Duo-core Meter Customized For Electrical Professionals!

Duo-core A+V, VFD V/Hz, AmpTip™ Jaws, In-rush Peak-RMS, °C/°F, DCμA, Ohms 6000kΩ, Motor RST, +Visible Continuity, Hi/Lo EF-Detection

TYPE-K TEMPERATURE (BM176D & 175D ONLY)
 Selectable °C And °F Readings;
 Comes With Bkp60 Bead Probe

Hi/Lo EF-DETECTION
 Both Non-Contact (NCV) &
 Single-Probe Voltage Detection
 For Identifying Live Lines;
 Selectable Hi/Lo Sensitivities

LVD CAT III 600V & CAT IV 300V
 Certified EN61010-2-032, EN61010-2-033,
 EN61010-1 & Relevant UL Standards On
 CAT III 600V & CAT IV 300V

ACA 30mm AmpTip™ CLAMP JAWS
 For Large & Small Conductors With
 AC TRMS 600A Capability

DIODE TEST
 For Testing Diodes & Rectifiers

DCμA (BM176D & 175D ONLY)
 For HVAC Flame Sensors
 Testing Via Test Probes

AUDIBLE + VISIBLE CONTINUITY
 For Quick Open-short Tests
 On Switches, Fuses, And Wires;
 Visible Flashing Icons

PHASE ROTATION (BM176D ONLY)
 Two Sensitivity RST Modes For
 Both Supply Systems And Motors

AUTO-POWER-OFF
 Extends Battery Life

CAPACITANCE
 2 Auto-ranges Up To 2500μF
 To Measure Motor Capacitors

FULLY AUTO-RANGING DMM
 Shortens The Time To Measure
 And Increases The Ease Of Use

6000kΩ RESISTANCE
 5 Auto-ranges Up To 6000kΩ
 Best Resolution 0.1Ω At 600Ω Range

VFD V & Hz FEATURE
 Measures Fundamental
 Voltage & Frequency Of Most
 Variable Frequency Drives

ERGONOMIC & STREAMLINE BODY
 Also Comes With A Soft Pouch
 For Easy Carrying & Protection

IN-RUSH PEAK-RMS
 Captures In-rush Peak RMS Readings
 At Durations As Short As 80ms

DUO-CORE MEASUREMENTS
 To Conveniently Measure Amps +
 Volts Or Another DMM Function

AmpTip™ LOW-CURRENTS
 Calibrated To Measure At Jaw Tip For
 Small-sized Conductors Up To 60 Amps

DATA HOLD
 Freezes The Displaying
 Reading For Later View

REGULAR CURRENT
 Measures At Jaw Center For
 Regular Conductors Up To 600 Amps

RUGGED & DURABLE
 High-impact Fire-retarded
 Enclosure With Battery
 Compartment & Access Door

BACKLIGHTED LCD DISPLAY
 For Easy Viewing In The Dark

EMC
 Meets EN61326-1:2013

TRANSIENT PROTECTION
 Up To 6kV 1.2/50μs Lightning Surge;
 More Confidence For Serious Users

1.0% DCV BASIC ACCURACY
 DCV Up To 600V;
 ACV Up To 600V



GENERAL SPECIFICATIONS

Display: 3-5/6 digits 6000 counts; dual display

Polarity: Automatic

Update Rate: 5 per second nominal

Operating Temperature: 0°C to 40°C

Relative Humidity: Maximum relative humidity

80% for temperature up to 31°C decreasing

linearly to 50% relative humidity at 40°C

Pollution degree: 2

Storage Temperature: -20°C to 60°C, < 80%

R.H. (with battery removed)

Altitude: Operating below 2000m

Temperature Coefficient: nominal 0.15 x

(specified accuracy) / °C @ (0°C - 18°C or 28°C -

40°C), or otherwise specified

Sensing: True RMS

Safety: Double insulation per UL/IEC/EN61010-1

Ed. 3.0, CAN/CSA C22.2 No. 61010-1 Ed. 3.0,

UL/IEC/EN61010-2-032 Ed. 3.0,

UL/IEC/EN61010-2-033 Ed. 1.0 to CAT III 600V

and CAT IV 300V AC & DC

Transient Protection: 6.0kV (1.2/50µs surge)

Overload Protections:

Clamp-on jaws: 600A rms continuous

* + & COM Terminals (all other functions):

600VDC/VAC rms

E.M.C.: Meets EN61326-1:2013

Temperature function at 80MHz ~ 150MHz:

In an RF field of 1V/m:

Total Accuracy = Specified Accuracy + 25 digits

Other functions:

In an RF field of 3V/m:

Total Accuracy = Specified Accuracy + 20 digits

Power Supply: 1.5V AAA Size battery X 2

Power Consumption: 6.2mA typical

Low Battery Indication:

Below approx. 2.85V for Capacitance & Hz

Below approx. 2.5V for other functions

APO Timing: Idle for 32 minutes approx.

APO Consumption: 5µA typical

Dimension (LxWxH): 217 x 76 x 37mm

Weight: 186gm

Jaw opening & Conductor diameter:

30mm max

Accessories: Test lead set, User's manual, Soft

carrying pouch, Bkp60 banana plug K-type

thermocouple (BM175D & BM176D only), Alligator

Clip set (BM176D only)

Optional purchase accessories: BKB32 banana

plug to type-K socket plug adaptor (BM175D &

BM176D only)

Special Features: AmpTip™ low-current range;

Display Hold; EF-Detection (NCV); Backlighted

LCD; 80ms Peak-RMS mode for inrush current;

3-Phase Rotation detection (BM176D only)

Electrical Specifications

Accuracy is ±(% reading digits + number of digits) or otherwise specified, at 23°C ± 5°C.

Maximum Crest Factor < 2.5 : 1 at full scale & < 5 : 1 at half scale or otherwise specified, and with frequency components within the specified frequency bandwidth for non-sinusoidal waveforms.

DC Voltage

RANGE	Accuracy
600.0V	1.0% + 5d

Input Impedance: 10MΩ, 100 pF nominal

AC Voltage (with Digital Low Pass Filter)

RANGE	Accuracy
50Hz ~ 60Hz	
600.0V	1.0% + 5d

Input Impedance: 10MΩ, 100 pF nominal

Hz Line Level Frequency

Function	Sensitivity ¹⁾ (Sine RMS)	Range
600V	50V	5.00Hz ~ 999.9Hz

Accuracy: 1% + 5d

¹⁾DC-bias, if any, not more than 50% of Sine RMS

Audible Continuity Tester

Audible Threshold: Between 10Ω and 250Ω

Response time: 32ms approx.

Ohm

RANGE	Accuracy
600.0Ω, 6.000KΩ, 60.00KΩ	1.0% + 5d
600.0KΩ ¹⁾ , 6000KΩ ²⁾	1.2% + 5d

Open Circuit Voltage: 1.7VDC typical

¹⁾Test Current: 2µA typical

²⁾Test Current: 0.2µA typical

Capacitance

RANGE	Accuracy ¹⁾
200.0µF, 2500µF	2.0% + 4d

¹⁾Accuracies with film capacitor or better

Diode Tester

RANGE	Accuracy
3.000V	1.5% + 5d

Test Current: 0.3mA typical

Open Circuit Voltage: < 3.5VDC typical

DCµA (BM175D & BM176D only)

RANGE	Accuracy	Burden Voltage
200.0µA, 2000µA	1.0% + 5d	3.5mV/µA

Temperature (BM175D & BM176D only)

RANGE	Accuracy
-40.0 °C ~ 99.9 °C	1.0% + 0.8°C
100 °C ~ 400 °C	1.0% + 1°C
-40.0 °F ~ 99.9 °F	1.0% + 1.5°F
100 °F ~ 752 °F	1.0% + 2°F

K-type thermocouple range & accuracy not included

AmpTip™ Clamp-on ACA

RANGE	Accuracy ¹⁾ ²⁾ ³⁾ ⁴⁾
50Hz ~ 60Hz	
60.00A	1.5% + 5d

¹⁾Induced error from adjacent current-carrying conductor: < 0.06A/A

²⁾Induced error from ACV measurement < 0.60A

/kV @ 50/60Hz

³⁾Add 10d to the specified accuracy @ < 6A

⁴⁾Unspecified @ < 0.2A while Rotary-switch

function is Continuity or Non-Contact EF-Detection

Regular Clamp-on ACA

RANGE	Accuracy ¹⁾ ²⁾ ³⁾ ⁴⁾
50Hz ~ 100Hz	
60.00A ⁵⁾ , 600.0A	1.8% + 5d
100Hz ~ 400Hz	
60.00A ⁵⁾ , 600.0A	2.0% + 5d

¹⁾Induced error from adjacent current-carrying conductor: < 0.06A/A

²⁾ Induced error from ACV measurement < 0.60A

/kV @ 50/60Hz

³⁾Specified accuracy is for measurements made at

the jaw center. When the conductor is not

positioned at the jaw center, add 2% to specified

accuracy for position errors

⁴⁾Unspecified @ < 0.2A while Rotary-switch

function is Continuity or Non-Contact EF-Detection

⁵⁾ Add 10d to specified accuracy @ < 6A

80ms PEAK-RMS for Clamp-on ACA functions

Response: 80ms to > 90%

Accuracy: share clamp-on ACA function specifications except unspecified for < 2% of range

Non-Contact EF-Detection

Bar-Graph Indication	EF-H (High Sensitivity)	EF-L (Low Sensitivity)
	Typical Voltage (Tolerance)	
-	10V (5V ~ 25V)	40V (32V ~ 70V)
--	25V (20V ~ 66V)	110V (55V ~ 165V)
---	55V (50V ~ 125V)	220V (130V ~ 265V)
----	110V (90V ~ 200V)	400V (250V ~ 500V)
-----	220V (>180V)	550V (>430V)

Indication: Bar-graph segments & audible beep tones proportional to the field strength

Detection Frequency: 50/60Hz

Detection Antenna: Top side of the stationary jaw

Probe-Contact EF-Detection: For more precise

indication of live wires, such as distinguishing

between live and ground connections, use direct

contact testing with one single test-probe via an

input terminal. The COM terminal (Black) has the

best sensitivity.



BRYMEN TECHNOLOGY CORPORATION

<http://www.brymen.com>

TEL: +886 2 2226 3396 (rep)

FAX: +886 2 2225 0025

Copyright © MMXV B.T.C. All rights reserved

Specifications subject to change without notice

Patents pending. Printed in Taiwan