



BM176D

Convenient Clamp DMM Duo

Hi/Lo EF-DETECTION

ACA 30mm AmpTip™ CLAMP JAWS

DCμA

PHASE ROTATION

CAPACITANCE

6000kΩ RESISTANCE

ERGONOMIC & STREAMLINE BODY

DUO-CORE MEASUREMENTS

DATA HOLD

RUGGED & DURABLE

1.0% DCV BASIC ACCURACY

TRANSIENT PROTECTION

EMC

BACKLIGHTED LCD DISPLAY

REGULAR CURRENT

AmpTip™ LOW-CURRENTS

IN-RUSH PEAK-RMS

VFD V & Hz FEATURE

FULLY AUTO-RANGING DMM

AUTO-POWER-OFF

AUDIBLE + VISIBLE CONTINUITY

DIODE TEST

LVD CAT III 600V & CAT IV 300V

TYPE-K TEMPERATURE Both Non-Contact (NCV) & Single-Probe Voltage Detection For Identifying Live Lines; Selectable Hi/Lo Sensitivities

For Large & Small Conductors With AC TRMS 600A Capability

For HVAC Flame Sensors Testing Via Test Probes

Two Sensitivity RST Modes For Both Supply Systems And Motors

2 Auto-ranges Up To 2500μF To Measure Motor Capacitors

5 Auto-ranges Up To 6000kΩ Best Resolution 0.1Ω At 600Ω Range

Also Comes With A Soft Pouch For Easy Carrying & Protection

To Conveniently Measure Amps + Volts Or Another DMM Function

Freezes The Displaying Reading For Later View

High-impact Fire-retarded Enclosure With Battery Compartment & Access Door

DCV Up To 600V; ACV Up To 600V

Up To 6kV 1.2/50µs Lightning Surge; More Confidence For Serious Users

Meets EN61326-1:2013

For Easy Viewing In The Dark

Measures At Jaw Center For Regular Conductors Up To 600Amps

Calibrated To Measure At Jaw Tip For Small-sized Conductors Up To 60 Amps

Captures In-rush Peak RMS Readings At Durations As Short As 80ms

Measures Fundamental Voltage & Frequency Of Most Variable Frequency Drives

Shortens The Time To Measure And Increases The Ease Of Use

Extends Battery Life

For Quick Open-short Tests On Switches, Fuses, And Wires; Visible Flashing Icons

For Testing Diodes & Rectifiers

Certified EN61010-2-032, EN61010-2-033, EN61010-1 & Relevant UL Standards On CAT III 600V & CAT IV 300V

Selectable °C And °F Readings; Comes With Bkp60 Bead Probe