



BRIGHT PEOPLE'S CHOICE



BM27s
AutoCheck DMM

ELECTRIC FIELD	EF-Detection (Non-Contact Voltage)
INTELLIGENT	Auto Power Off
LINE-VOLTAGE HZ	With 3 Trigger Levels (V Position)
STANDARD	Hi-Z DCV & ACV 6V To 600V, 3 Ranges
DIODE TEST	Yes
AUDIBLE CONTINUITY	Yes
OHMS	600Ω RANGE
MICRO-AMPS AC/DC	400.0μA To 2000μA For Flame Sensors
EMC	MEETS EN61326:2013
TRANSIENT PROTECTION	Up To 4kV 1.2/50μs Lightning Surge
INPUT PROTECTION	600V On All Functions
LVD	Meets EN61010-1/-2-030/-2-033 CAT III 300V & CAT II 600V
FUNCTION SELECTOR	Yes
HOUSING MATERIAL	Fire-Retarded, UL Listed
FREQUENCY	10Hz To 30kHz (Auto-VΩ Position)
CAPACITANCE	100nF To 2000μF, 5 Ranges
AUTOCHECK OHMS	6kΩ To 6MΩ, 4 Ranges
AUTOCHECK	Lo-Z DCV & ACV 6V To 600V, 3 Ranges
AUTOCHECK FEATURE	Automatic DCV, ACV & OHMS Selection
DATA MEASUREMENT	5/Sec Fast
LARGE EASY TO READ LCD DISPLAY	6,000 Counts
FULLY AUTO-RANGING	Yes