

BM251s

Practical Multimeter

| <u> </u> | UTO · v | | rital Multin | | |
|----------|----------------------|-----------|--------------|--|---|
| | | | | MΩ kHz | |
| Ē | | | | ₩VA | |
| | | | Hz | EF. | |
| 1 K | SELECT | RANGE | REL | HOLD | |
| | () v . | ⊽ ™Ω | ‴ mV≅ | E A ≅ | |
| | OFF | | | µA≖ | ₹ |
| | | | | | |
| | iÀCK | | | | |
| | ΑμΑ | | = | Ων | |
| | | JACK A | сфм | | |
| | MAX 0.6A BC FUSED | MAX 1 | | | |
| | PC-Con | | | OV CAT IV J OV CAT III kV CAT II | |

ASIC More Functions & Features TECHNOLOGY At Affordable Prices

LARGE 6000
COUNTS LCD 5/Sec Fast Nominal Updata Rate
DISPLAY

HIGH ACCURACY 0.2% Basic DCV Accuracy

ANALOG BAR-GRAPH Fast Update Rate 40/Sec

LOGIC LEVEL Hz Measures Hi Frequency (mV FUNCTION) Logic Signals

LINE LEVEL Hz (V Measures Noisy High Voltage FUNCTION) ACV Frequencies

Both Non-Contact (NCV) &
EF-DETECTION Single-Probe Voltage Detection
For Identifying Live Lines

DATA HOLD Freezes The Displaying Reading For Later View

AUTO-POWER-OFF To Extend Battery Life

ERGONOMIC STREAMLINE DESIGN

Fits Comfortably In One's Hand

TRANSIENT Up To 6kV 1.2/50µs Lightning Surge; PROTECTION Superb Protection For Serious Users

EMC Meets EN61326-1:2013

LVD SAFETY Meets EN61010-1/-2-030/-2-033
CAT II 1kV, CAT III 600V & CAT IV 300V

RUGGED & High-Impact Fire-Retarded Enclosure DURABLE For Reinforced Safety & Durability

PC INTERFACE
CAPABILITY
Optional Purchase RS232C+USB Cables
With DATA Recording PC Software
For Win7/8/10

PROTECTIVE With Holders For Probe Storage

HOLSTER And "Third Hand" Feature
Replaceble & Washable

BEEP-JACK

AUDIBLE
WARNING

Beeps Against Improper Current Terminals
Plug In. Decreases Risks Of Damage

FAST AUDIBLE For Quick Open-Short Tests
CONTINUITY On Switches, Fuses, And Wires

DIODE TEST For Checking Diodes & Rectifiers

HIGH IMPEDANCE VOLTAGE

1000VAC/DC Measuring Capabilities; High Input Impedance For Load Sensitive Circuits

FUNCTION Toggle Conveniently Between SELECTION Primary & Secondary Functions

AUTO & MANUAL- Auto-Ranging With

AUTO & MANUAL- Auto-Ranging With RANGING Manual-Ranging Override

HIGH SPEED Shortens The Time To Test
AUTO-RANGING And Increases The Ease Of Use