



BM2803CSE

Practical Multimeter

26mm Large digit LCD 3-5/6 Digits 6,000 Counts Nominal

Fast Auto-Ranging Nominal 5/Sec Fast Measurements

Relative Zero To Offset Measurement Readings

BeepLit™ Continuity Features Audible Beep &

Visible Backlight Effects

Warm LED Backlight LCD Display

Features BeepPass™ (Short-beep) & BeepLit™ Diode Tester

BeepLit™ (Continuity)

To Warn Against On-hold Readings

Input Warning Against Improper BeepJack™ InEr Plug into µAmA/A Terminals

Detachable Protective Features Probe-Holders & Tilt-Stand

HBC 1kV Fuses Protected on µAmA & A Terminals

Captures Max Readings as High as MAX-hold 40 Conversions per Second

Hold-alert™

iAPO Intelligent Auto Power Off

Fire Retarded Housing Rugged with Battery Compartment Door

AC Conversions

Double-sided EMI For Harsh Electromagnetic Shielding Interfering Environments

EMC Certified To EN61326-1

Data-hold with

True RMS

DC/AC μA , mA, & A Ranges 600.0µA to 10.00A

Speeded Resistance Ranges 600.0Ω to $60.00M\Omega$

High Resolution Ranges 60.00mV to 600.0mV DC/AC mV

DC Voltage Ranges 6.000V to 1000.0V

AC Voltage Ranges 6.000V to 1000.0V

8kV Transient

Against 1.2/50µs + 8/20µs Combo Surges Protection

UL Listed & To EN61010-2-033 CAT III 1000V & LVD Certified CAT IV 600V