



BM2805CSE

Practical Multimeter

26mm Large digit LCD 3-5/6 Digits 6,000 Counts Nominal

Fast Auto-Ranging Nominal 5/Sec Fast Measurements

Relative Zero To Offset Measurement Readings

BeepLit™ Continuity Features Audible Beep &

Tester Visible Backlight Effects

Warm LED Backlight LCD Display

Features BeepPass™ (Short-beep) & BeepLit™ Diode Tester

BeepLit™ (Continuity)

From 5.00Hz to 300.0kHz Logic Frequency

Measures Fundamental V & VFD-V & VFD-Hz Hz of Most Variable Frequency Drives

Line Frequency From 10.00Hz to 50.00kHz

Input Warning Against Improper BeepJack™ InEr Plug into µAmA/A Terminals

Detachable Protective

Holster

Data-hold with

Features Probe-Holders & Tilt-Stand

HBC 1kV Fuses Protected on µAmA & A Terminals

Captures Max Readings as High as MAX-hold

40 Conversions per Second

To Warn Against On-hold Readings Hold-alert™

nF Ranges 20.00 to 2000, Speeded Capacitance μF Ranges 20.00 to 2000

True RMS AC Conversions

iAPO Intelligent Auto Power Off

Rugged with Battery Compartment Door Fire Retarded Housing

Double-sided EMI For Harsh Electromagnetic Shielding Interfering Environments

EMC Certified To EN61326-1

DC/AC µA, mA, & A Ranges 600.0µA to 10.00A Speeded Resistance Ranges 600.0Ω to $60.00M\Omega$

High Resolution Ranges 60.00mV to 600.0mV DC/AC mV DC Voltage Ranges 6.000V to 1000.0V

Ranges 6.000V to 1000.0V AC Voltage 8kV Transient

Against 1.2/50µs + 8/20µs Combo Surges Protection

UL Listed & To EN61010-2-033 CAT III 1000V & LVD Certified CAT IV 600V