



BRIGHT PEOPLE'S CHOICE



### BM906s

Versatile Multimeters

FULLY AUTO-RANGING	Shortens The Time To Measure And Increases The Ease Of Use
MANUAL-RANGING MODE	Auto-Ranging With Manual-Ranging Override
6000 + 999 COUNTS DUAL DISPLAY	Simultaneous Measurements Of ACA+Hz Or ACV+Hz
5/S FAST MEASUREMENT	Display Updates 5 Per Second Nominal For Fast Changes
RELATIVE ZERO MODE	For Convenient Readings Comparison & Offset
5ms CREST-MAX	Captures Peak Signals Of Volts/AMPS As Short As 5ms In Duration
DATA HOLD	Freezes The Displaying Reading For Later View
FULL CURRENT RANGES	DCA 6 Ranges To 10A, 20A For 30S ACA 6 Ranges To 10A, 20A For 30S
AUTO-POWER-OFF	Extends Battery Life
TRANSIENT PROTECTION	Up To 6kV 1.2/50μs Lightning Surge; More Confidence For Serious Users
LVD MEASUREMENT CATEGORY	Meets EN61010-1/-2-030/-2-033 CAT II 1kV, CAT III 600V & CAT IV 300V
EMC DIRECTIVE	Meets EN61326-1:2013
PROTECTIVE HOLSTER	Increases Product Durability; Washable & Replaceable
RUGGED & DURABLE	High-Impact Fire-Retarded Enclosure With Battery Compartment & Access Door
BEEP-JACK	Audible & Visible Input Warning Against Improper Plug In
VFD V & Hz FEATURE	Measures Fundamental Voltage & Frequency Of Most Variable Frequency Drives
LINE LEVEL (DUAL DISPLAY) Hz	Measures Noisy Line Level Voltage ACV Frequency
1kV VOLTAGE MEASUREMENT	Improved Measuring Capabilities DCV 5 Auto-Ranges To 1000V ACV 5 Auto-Ranges To 1000V
TYPE-K TEMPERATURE	Selectable °C And °F Readings; Optional Purchase BKP60 Bead Probe
EF-DETECTION	Both Non-Contact (NCV) & Single-Probe Voltage Detection For Identifying Live Lines
RESISTANCE	6 Auto-Ranges Up To 60MΩ
DIODE TEST	For Testing Diodes & Rectifiers
CAPACITANCE	6 Auto-Ranges Up To 3000μF To Measure Motor Capacitors
AUDIBLE CONTINUITY	For Quick Open-Short Tests On Switches, Fuses And Wires
LOGIC LEVEL Hz	Up To 0.001Hz Resolution Logic Level Frequency