



BT-71EU Electrical Tester

AUTOMATIC DCV. ACV & CONTINUITY SELECTION

INTELLIGENT AUTO ON & OFF

SCREW-ON STATIONARY (RED)

PROBE BODY

DETACHABLE(BLACK) TEST LEAD

19mm PROBE PITCH

IP2X 4mm TIPS DETACHABLE PROBES

EF-DETECTION

Optional 2mm+CAP/4mm For Mere IEC61010

EMC Meets EN61326-1:2013

> Both Non-Contact & Single-Probe Voltage Detection For Identifying Live Lines And Thus The Polarity

Shortens The Time To Test And Increases

Automatic Power On & Power Off To Extend

Standard 4mm Plug Design For Easy User

Spring Retractable Shrouded 4mm TIPS For

IEC61010 + IEC61243-3 Ed. 3 Version;

Screw-On Design For Easy User

For European Receptacle Testing

The Ease Of Use

Battery Life

Replacement

Replacement

ERGONOMIC STREAMLINE DESIGN

Fits Comfortably In One's Hand

UP TO 1kV VOLTAGE TESTING

Improved Testing Capabilities

DOUBLE INJECTION HOUSING

Seamless Over-Molded Push-Button Switches And LED / LCD Display Windows For Harsh Environments

DC AND AC INDICATIONS +V Lights Up For Correct DC Polarity, -V Lights Up For Reversed DC Polarity Both +V & -V Light Up For AC Indication

TRANSIENT Up To 8kV 1.2/50µs Lightning Surge; Superb

PROTECTION LVD CAT III & CAT IV Protection For Serious Users

SAFETY

Meets EN61010 And EN61243-3 ED. 3, To CAT III 1000V & CAT IV 600V

BATTERY-LESS VOLTAGE DETECTION

LEDs Indicate The Presence Of Voltages With Power Supplied By The Test Object, Without The Need Of Battery Power

ELV LIMIT INDICATION (BATTERY-LESS)

The LED Indicates The Presence Of A Voltage Beyond The ELV Limit (120 VDC/50 VAC) With Power Supplied By The Test Object, Without The Need Of Battery Power

AUDIBLE CONTINUITY

For Quick Open-Short Tests On Switches, Fuses, And Wires